

XE155WECR

Applications : Municipal gardening, road maintenance, pipeline laying, earthwork transfer.

Features : XCMG's first 15-ton short-tail wheel excavator has a family-style appearance design, a compact overall layout, and a customized machine attachments confluence function. It can be equipped with hydraulic wrists and other attachments to meet the needs of various working conditions.



Never attempt to lift or hold any load in excess of the rated lifting capacity at the specified lifting radius and height. The lifting point is located on the lifting eye of the arm (Bucket weight is not included), any additional attachment such as bucket should be deducted from the lifting weight. When determining the net lifting weight allowed for the machine, the weight of the slings and any auxiliary lifting devices must be deducted from the rated lifting capacity. Lifting capacity is based on the machine standing on firm and level ground. The operator should consider working conditions such as soft or uneven ground. Before operating the machine, the operator should familiarize himself with the safety procedures in the relevant manual.

 		 kg										Front radial blade Rear outriggers (U= support up/D= support down)										
 In travel direction		 Against travel direction								 Right angle to travel direction												
LD	Y X	1.5m				3.0m				4.0m				5.0m				MAX				m
																						
2.51m		U	D	U	D	U	D	U	D	U	D	U	D	U	D	U	D	U	D	U	D	
	Z2									*3000	*3000	*3000	*3000	2400	2400	2400	2400	2000	*2000	2000	*2000	7.2
	Z1									*7200	*7200	6500	*7200	*4900	*4900	3500	*4900	*2500	*2500	1900	*2500	7.4
	Z3					*8900	*8900	5400	*8900	5300	*6200	3000	*5300	3500	*4500	2000	3700	2700	*2800	1600	2800	7.1